

Manganese Colorimetric Online Analyzer

CL943

CL943 is a microprocessor controlled online analyzer specifically designed for automatic Manganese monitoring on several types of waters matrix.

* Easy configuration

With our modular configuration we can automate your color laboratory method with up to four reagents

* Dual compartment enclosure

To ensure complete separation between electronics and hydraulics

* Touch screen interface

Simple and user friendly menus and functions

* Separate waste line for sample containing reagents

* Long autonomy, low maintenance, low operating cost

* Rugged and reliable

Designed for industrial and environmental on-line applications, ensures the highest level of robustness in the electronics, mechanics and hydraulics components

* Easy installation and operation

To start measurement is enough to power the analyzer and connect reagents, sample and waste line.

* Loss of sample input

* Low reagent level alarm

Benefit:

* Programmable photometer

* Low measurement range


* Automatic calibration / validation / cleaning

* Free selectable measuring, cleaning and calibration intervals



Measuring Principle and Hydraulics diagram

After rinsing the cuvette, sample will pump into dilutor followed by distilled water into the Cuvette. Mixing pump will then activated to mix the sample with distilled water (Dilution process applies to high range models only. For low range models sample will pump directly into Cuvette).



First measurement take place (reference) to eliminate interfering factors such as sample own colour or turbidity, miscellaneous reagents own colour and refractive index variations.

Next Reagent 1, 2 and 3 will add into cuvette, and mixing pump will activate to mix the liquid from lower part to the upper part of the cuvette. Color development and second measurement take place.

The concentration is measured with the absorbance calculated based on the difference between the two measurements and the stored calibration parameters.

Technical Specifications:

| | |
|---------------------------|---|
| Measuring Principle | Colorimetric |
| Colorimeter | LED (Specific wavelength), Photodetector, Thermostated measuring cell |
| Measurement type | Cyclic |
| Measurement Interval | Programmable |
| Measurement time | About 15 min |
| Range | 0-100 µg/L, 0-1.0; 0-5.0 mg/L |
| Detection Limit | ≤2% of the full scale |
| Repeatability | ±2% on absorbance value with turbidity < 80 NTU |
| Output signal | 4-20mA, RS232 |
| Input signals | 2 configurable relays |
| Alarms | 2 configurable relays |
| Sample and waste delivery | No pressure |
| Reagents consumption | 2500 measurement/liter/each |
| Sample Temperature | 5-50°C |
| Protection | IP55 |
| Hardware | Color touch screen |
| Power Supply | 220VAC , 50-60 Hz, 80VA |
| Weight | Approx. Kg. 17 kg. |
| Dimension | 380 x600 x210 mm (W*H*D) |